



Durable ABS Cabinet With Graceful Curves



Zealux model		XP075DCsiPBS32	XP095DCsiPBS32	XP125DCsiPBS32	XP165DCsiPBS32	XP215DCsiPBS32	XP255DCsiPBS32
Advised pool volume (with pool cover)	m ³	10-25	12-33	15-60	25-85	55-120	65-130
* Performance at Air 28°C, Water 28°C, Humidity 80%							
Heating capacity	kW	7.5-2.2	9.5-2.3	12.5-2.9	16.5-3.8	19.5-4.7	24.5-5.9
Power consumption	kW	1.3-0.14	1.55-0.14	2-0.18	2.75-0.24	3.25-0.29	4.08-0.37
C.O.P.		16-5.6	16-5.8	16-6.2	16-6	16-6	16-6
* Performance at Air 15°C, Water 26°C, Humidity 70%							
Heating capacity	kW	4.7-2.5	6.6-1.9	8.5-2	11.2-3	14-3.9	17.2-4.5
Power consumption	kW	1.02-0.35	1.43-0.27	1.89-0.28	2.43-0.42	2.78-0.54	3.74-0.63
C.O.P.		7.1-4.5	7.1-4.5	7.2-4.5	7.2-4.5	7.2-4.5	7.2-4.5
* General dat							
Compressor type		Inverter compressor					
Voltage	V	220-240V/50Hz or 60Hz/1PH					
Rated current	A	5.8	6.9	8.9	12.2	14.4	18.1
Minimum fuse	A	9	10	14	18	22	27
Advised water flux	m ³ /h	2.5	2.8	3.7	4.6	5.0	8.0
Water pressure drop	Kpa	12	12	14	15	18	20
Heat exchanger		Twist-titanium tube in PVC					
Water connection	mm	50					
Fan quantity		1					
Ventilation type		Horizontal					
Fan speed	RPM	500-850					
Noise level(10m)	dB(A)	≤41	≤42	≤42	≤43	≤45	≤46
Noise level(1m)	dB(A)	40-50	40-52	40-52	41-54	41-54	42-60
* Dimension/ Weight							
Net weight	kg	56	68	68	98	117	128
Gross weight	kg	68	73	73	113	135	146
Net dimension	mm	855*325*565		986*352*672		1040*355*895	
Packing dimension	mm	942*375*695		1066*426*835		1095*405*1025	

The data above is just for reference. For model specifications, please refer to the nameplate on the unit.